

Confidential Report

Our Ref: 53472-7-2



Notified Body for PPE Directive, Construction Products Regulation & Marine Equipment Directive I.D. No. 0338 & 0339



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999 Email: <u>info@bttg.co.uk</u>

Website: www.bttg.co.uk

Date: 31 May 2017

Our Ref: 53472-7-2 Your Ref: 1333

Page: 1 of 5

Client: Kobefab Interntional B.V.

De Vest 62

5555 XP Valkenswaard

Netherlands.

Job Title: Fire Test on One Sample of Fabric

Client's Order No: 1333

Date of Receipt: 10 May 2017

Description of Sample(s): Toucan, stated to be 44% pan, 11% pes, 30% KDK pes, 6% vi

Work Requested: We were asked to make the following test(s):

IMO FTP Code 2010 Part 8 (Upholstered Furniture)

- subcontracted test, UKAS accredited
- ** subcontracted test, EN ISO/IEC 17025 accredited
- *** not UKAS accredited





Email: info@bttg.co.uk

Website: www.bttg.co.uk

Date: 31 May 2017

Our Ref: 53472-7-2 Your ref: 1333

> Page: 2 of 5



Client: Kobefab Interntional B.V.

Product Description Sheet

Type of Furniture, e.g., Seat, Sofa, Office Chair, etc;.	Seat, sofa, office chair etc	
Name and/or Identification of the Product Tested	Toucan	
Materials of the Product and its Composite Ratio (i)	44% Pan, 11% Pes, 39% KDK Pes, 6% Vi	
Composition of Weave (ii)	Yarn dyed velvet	
Density (Number/Inch) the Number of Threads per Inch in both warp and weft; and		
Yarn Number Count		
Thickness (mm)	1-2mm	
Mass per Unit Area (g/mm²)	Approx. 450 gr/sqmtr	
Colour and Tone (iii)	-	
Method and Quantity of Fire Retardant Treatment	Backcoated	

- Such as wool, nylon, polyester, etc.
- (ii) Such as plain, weave, twilled.
- (iii) If the product has a pattern, the representative colour shall be described.





Wira House, West Park Ring Road, Leeds, LS16 6QL, UK. Telephone: +44 (0) 113 259 1999

Email: info@bttg.co.uk

Website: www.bttg.co.uk

Date: 31 May 2017

Our Ref: 53472-7-2 Your ref: 1333

Page: 3 of 5

Client: Kobefab Interntional B.V.

FIRE TESTS ACCORDING to IMO FTP Code 2010 : Part 8

Test for Upholstered Furniture

Date of test: 25/5/2017

Conditioning

Immediately prior to testing the sample was placed in indoor ambient conditions for 72 hours and then conditioned in a standard atmosphere of $20 \pm 5^{\circ}$ C temperature and $50 \pm 20\%$ relative humidity for at least 16 hours.

The sample was tested in a room of volume 25m³ and 21 °C.

Procedure

The sample was tested in accordance with IMO FTP Code 2010:Part 8 using ignition sources 0 and 1. The sponsor sampled the material and the specimens were cut from the sample received to the dimensions set out in the standard.

The specimens were mounted over fillings of standard non-FR polyurethane foam of density about 22Kg/m³.

Requirements

No progressive smouldering or flaming within one hour of the placement of the cigarette.

All progressive smouldering and flaming to cease within 120sec of removal of the burner tube.





Wira House, West Park Ring Road, Leeds, LS16 6QL, UK. Telephone: +44 (0) 113 259 1999

Email: info@bttg.co.uk Website: www.bttg.co.uk

Date: 31 May 2017

Our Ref: 53472-7-2 Your ref: 1333

> Page: 4 of 5

Client: Kobefab Interntional B.V.

Results

	Specimen 1		Specimen 2	
Ignition Source	0	1	0	1
Ignition Time (secs.)	-	2	-	2
Extinction Time (Flame) (secs.)	-	40	-	2
Extinction Time (Smoke) (secs.)	26	-	29	-
Time of Cover Split (secs.)	DNS	16	DNS	14
Progressive smouldering/flaming observed	No	No	No	No
Performance	PASS	PASS	PASS	PASS

DNP - Did not propagate ME - Manually extinguished DNS - Material did not split BES - Burnt to edge of specimen

EC – Escalating combustion ES - Escalating smouldering DNO - Did not observe time of event BTTF - Burnt through thickness of foam

Note

The test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Comment

In our opinion, based on the test carried out on the sample supplied; the results indicate the sample meets the requirements according to IMO 2010 FTP Code, Part 8.

Reported by:.. J Coleman Fire Technician

Countersigned By:.. P Doherty Operational Head

Enquiries concerning this report should be addressed to Customer Services.





Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999

Email: <u>info@bttg.co.uk</u> Website: <u>www.bttg.co.uk</u>

Date: 31 May 2017

Our Ref: 53472-7-2 Your ref: 1333

Page: 5 of 5

Client: Kobefab Interntional B.V.

Uncertainty Budget - Annex

The overall uncertainty budget IMO FTP Code 2010:Part 8 is as follows:-

Measurements: ±1mm
Timings: ±2 seconds

